

Carpentry table saw

TKS-Z 400

Ideal for longitudinal cuts, chop cuts and miter cuts on larger wooden beams



Article number ▼

5741400

Brand ▼

Holzkraft

Availability ▼

In stock

Immediate delivery

Catalog directory ▼

Woodworking machinery » Circular saw /

Sliding table saws » Table Saws

Purchase ▼

Minimum 1 pc(s).



Delivery content ▼

- Carbide saw blade 400 x 4.0 x 30 mm, Z 28
- Riving knife 3.8 mm
- Riving knife 2.8 mm
- Saw blade guard with dust extraction
- Chassis
- Tool box
- Push stick
- Operating tool

Shipping informations ▼

Packaging Metrics		Weights		Delivery		Other	
Length	1,100 mm	Gross	164 kg	Delivery	Carrier	DualUse	✗
Width	910 mm	Net	131 kg	Content	1 pc(s).	SCIP	n/a
Height	970 mm					SVHC	No

Root data ▼

Country of origin		EAN	Customs Tariff Number	Quantity unit
	China	4036351276609	84659120	pc(s).

Video ▼

www.youtube.com/watch?v=LpSMVEdMtPU

Description ▼

- Saw blade can be swivelled up to 45° and rotated by up to 90°
- Tilt of the sawing unit via hand lever and scale
- Guidance of the sawing unit for cut cuts from bottom to top via a lever
- Suitable for creating throat and burr rafters as well as eaves and wedge planks
- Parallel stop with scale
- Saw blade cover and working unit with suction connection 100 mm
- Toolbox on the machine frame for clean storage of the tool
- Chassis and hand lever facilitate transport
- Boom set available as an accessory to greatly facilitate work with long workpieces

Manufacturer

Stürmer Maschinen GmbH
Dr.-Robert-Pfleger-Str. 26, 96103 Hallstadt, Germany
info@stuermer-maschinen.de

Media informations ▼



Saw blade rotation of up to 90° (illustration shows extension arm set available as accessory, 5741404)



Saw blade rotation of up to 90° (illustration shows extension arm set available as accessory, 5741404)



Shift cut

Technical data ▼

Dimensions and weights			
Length (product) approx.	1350 mm	Width/depth (product) approx.	1100 mm
Height (product) approx.	1180 mm	Net weight approx.	131 kg
Extraction port			
Extraction port diameter bottom	100 mm	Saw blade protection extraction port diameter	100 mm
Installation information			
Transport width	1100 mm	Length	910 mm
Width/depth	970 mm		
Electrical Data			
Supply voltage	400 V	Mains frequency	50 Hz
Absorbed power drive motor	2,8 kW	Output power (motor power)	2,2 kW
Protection class drive motor	IP44	Duty type drive motor	S1
Motor speed	2800 min ⁻¹	Total current draw	5,5 A
Sliding carriage and table			
Sliding table length	560 mm	Sliding table height	140 mm
Sliding table width	40 mm	Table length	945 mm
Table width	715 mm	Work height	845 mm
Noise emission			
Sound pressure level	80,7 dB(A)	Sound power level	96,7 dB(A)
Circular saw unit			
Max. cutting width with rip fence	640 mm	Max. cross cut width left from saw blade	410 mm
Saw blade angle	90 45 °	Max. cutting height 90°	120 mm
Max. cutting height 45°	90 mm	(Main) saw blade diameter	400 mm
(Main) saw blade speed	2800 min ⁻¹		

Accessories ▼



Cut-to-size alternating teeth circular saw blade KSB-WZ 400/36



Article number ▼
5264036

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Edging and production cut circular saw blade KSB-BF 400/96



Edging and production cutting circular saw blade with highest quality level especially for industrial applications on stationary machines

Article number ▼
5264096

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Boom set for TKS-Z 400



Article number ▼
5741404

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



HM saw blade 400 x 30 x 4 mm Z28



Article number ▼
5741405

Availability ▼
No stock available
Information:
Next availability
Expected on
calendar week
43/2026

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Protractor WM 90-4



Article number ▼
5910094

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.