GLOBAL
VACUUM PRESSES

VP-P Vacuum Press Professional

6 configurations
Pressing areas up to 3740 × 1620 mm

40 m³/h
Professional vacuum pump

Up to 32 suction points
Uniform vacuum distribution

CE compliant
EU Conformity



MODELS & SPECIFICATIONS

MODEL	PRESS AREA	MAX. POWER	DIMENSIONS (MM)
VP-P-2514	2540 × 1420 mm	1.25 kW	2720 × 1530 × 980 mm
VP-P-3114	3140 × 1420 mm	1.25 kW	3320 × 1530 × 980 mm
VP-P-3714	3740 × 1420 mm	1.25 kW	3920 × 1530 × 980 mm
VP-P-2516	2540 × 1620 mm	1.25 kW	2720 × 1740 × 980 mm
VP-P-3116	3140 × 1620 mm	1.25 kW	3320 × 1740 × 980 mm
VP-P-3716	3740 × 1620 mm	1.25 kW	3920 × 1740 × 980 mm

ABOUT THIS MACHINE

The VP-P Vacuum Press Professional is a robust vacuum membrane press designed for daily professional production. Its rigid laser-cut metal chassis, 40 m³/h vacuum system and 18 mm compact HPL worktop provide stable and uniform pressure for demanding workshop applications.

KEY FEATURES

Professional production design
Rigid laser-cut chassis
40 m³/h vacuum system
Uniform vacuum distribution
Automatic vacuum control
Flexible membrane options
Mobile workshop configuration

WHY GLOBAL VACUUM PRESSES

- **35+ years** vacuum forming expertise
- Direct technical support in **5 languages**
- European manufacturer with no intermediaries
- Standard and custom-built vacuum solutions
- More than **200 customers worldwide**

STANDARD SPECIFICATIONS

Operation	Manual · automatic/off/continuous vacuum control
Vacuum pump	40 m³/h rotary vane
Max. pressure	8.5 t/m² · 150 mbar abs. · approx. 85% vacuum
Worktop	18 mm compact HPL · up to 32 suction points
Air evacuation	Integrated grid pattern
Membrane	2 mm natural rubber / silicone
Working height	900 mm
Supports	4 industrial swivel wheels · 2 with brakes
Electrical supply	400 V · 3-phase · 50 Hz
Weight	375–480 kg, depending on model
Documentation	CE Declaration of Conformity · CO on request

OPTIONAL FEATURES

· 250 mm high volume silicone membrane
· 500 mm high volume silicone membrane
· Optional polyurethane membrane for 1420 mm
· 300 L vacuum tank with T-ball valve
· Becker or Busch oil-lubricated vacuum pump
· UL/CSA dry-running vacuum pump
· External vacuum connection
· Digital vacuum switch
· 140 or 160 cm protective cover
· Vacuum-assisted quick-opening top frame

NR = Natural rubber
SI = Silicone membrane