GLOBAL
VACUUM PRESSES

VP-T Vacuum Press Turntable

40 m³/h
Professional vacuum capacity

3 models
Dual up to 2x 3740 x 1440 mm

Twin-table system
Alternating serial production

CE compliant
EU Conformity



ABOUT THIS MACHINE

The VP-T Vacuum Press Turntable is an industrial twin-station vacuum membrane press developed for serial production and efficient workflow. Its motor-driven rotating table allows one pressing area to be prepared or unloaded while the opposite station is ready for the next production cycle.

KEY FEATURES

Twin-station production system
Motor-driven rotation
Industrial serial production
Two independent vacuum controls
Rigid laser-cut chassis
Uniform vacuum distribution
Professional vacuum capacity

WHY GLOBAL VACUUM PRESSES

- **35+ years** vacuum forming expertise
- Direct technical support in **5 languages**
- European manufacturer with no intermediaries
- Standard and custom-built vacuum solutions
- More than **200 customers worldwide**

MODELS & SPECIFICATIONS

MODEL	PRESS AREA	MAX. POWER	DIMENSIONS (MM)
VP-T-2514	2 × 2540 × 1440 mm	2 kW	3630 × 1680 × 1170 mm
VP-T-3114	2 × 3140 × 1440 mm	2 kW	4230 × 1680 × 1170 mm
VP-T-3714	2 × 3740 × 1440 mm	2 kW	4870 × 1680 × 1170 mm

STANDARD SPECIFICATIONS

Operation	Manual · automatic/off/continuous vacuum control
Rotation	Electric gear-motor drive
Vacuum control	2 independent control valves
Vacuum pump	40 m³/h rotary vane
Max. pressure	8.5 t/m² at 150 mbar abs. · approx. 85% vacuum
Worktops	18 mm compact HPL · up to 32 suction points*
Air evacuation	Integrated grid pattern
Membrane	2 mm natural rubber / silicone
Working height	Approx. 900 mm
Supports	Adjustable anti-slip feet
Weight	980–1125 kg, depending on model
Electrical supply	400 V · 3-phase · 50 Hz
Documentation	CE Declaration of Conformity · CO on request

OPTIONAL FEATURES

· Two 250 mm high-volume silicone membranes
· 40 m³/h Becker oil-lubricated vacuum pump
· 40 m³/h Busch oil-lubricated vacuum pump
· Digital vacuum switch

NR = Natural rubber | SI = Silicone membrane