Edge bander

minimax me 35tr

With corner copying function, for plastic edges of 0.4 - 2 mm, solid wood edges up to 3 mm and workpieces of 8 - 50 mm

Article number
5507135

Brand
Holzkraft



Availability
In stock
Immediate delivery

Catalog directory
Woodworking machinery » Edge banding machines » Edge banding machines

Purchase
Minimum 1 pc(s).

Delivery content
Diamond tools for the roughing unit

Shipping informations

Packaging Metrics		Weights		Delivery		Other	
Length	3,314 mm	Gross	545 kg	Delivery	Special transportation	DualUse	✖
Width	1,085 mm	Net	545 kg	Content	1 pc(s).	SCIP	n/a
Height	1,300 mm					SVHC	No

Root data

Country of origin	EAN	Customs Tariff Number	Quantity unit
Italy	4036351313304	84659900	pc(s).

MADE IN ITALY

Description

- Convenient and easy control of all important functions via control panel on the front
- Excellent accessibility to the working units thanks to large hood, which provides additional protection and noise reduction.
- Precise and proven units enables optimum machining and perfect edge finishing
- Joining unit equipped with two slide cutters
- High-frequency motors for edge processing
- Standard equipped with radius and surface scraper
- Optional extendable either by buffing or roller grooving unit with max. groove width 4.0 mm
- Available in different equipment variants to adapt to individual requirements
- Automatic temperature reduction of the glue unit at longer idle time of machine
- Standard equipment with glue container made of aluminum for EVA hot melt adhesive

Manufacturer
SCM Group S.p.A Div. MINIMAX
Via Casale 450, 47826 Villa Verucchio (RN), Italy
minimax@scmgroup.com

Media informations








Control panel

- Attached to front panel
- All functions are quick and easy to recall




Pre-milling unit

- Two diamond cutters
- Insert controlled




Glue Station

- Fast and uniform heating of the hot melt adhesive by heating rods that are located both in the glue pot and in the applicator roll




Pressing unit

- Two metal rollers press the edge evenly onto the workpiece
- Large roller is spring-mounted and ensures good heat dissipation so the glue sets faster




Corner rounding unit

- No need for rework on corners




Flush radius milling unit

- Combination Milling Tool for high quality machining and versatility
- Horizontal and vertical guide rollers for edge finishing
- High-frequency motors ensure optimum quality
- Simple, precise setting and high repeatability via digital counter



Radius scraper

- For the perfect finish of plastic edges
- With device to reset the unit if it is not needed



Surface Scraper

- For the perfect finish of plastic edges
- With device to reset the unit if it is not needed



Conveyor belt with chain

Technical data

Dimensions and weights			
Length (product) approx.	3314 mm	Width/depth (product) approx.	1085 mm
Height (product) approx.	1300 mm	Net weight approx.	545 kg
Flush radius milling unit			
Flush radius milling unit current draw	2 x 0.35 kW	Flush radius milling unit miller diameter HM	55.3 mm
Flush radius milling unit miller speed	12000 min^{-1}	Flush radius milling unit extraction port diameter	60 mm
Flush radius milling unit number of extraction ports	2		
Corner copy unit			
Corner copy unit current draw	0.35 kW	Corner copy unit tool diameter	58 mm
Corner copy unit speed	12000 min^{-1}		
Electrical Data			
Supply voltage	400 V	Mains frequency	50 Hz
Gluing unit			
Glue pot current draw	0.18 kW	Glue pot operating temperature	190 °C
Glue pot extraction port diameter	60 mm	Glue pot filling quantity	0.8 kg
Pneumatic connection			
Operating pressure	6.5 bar		
Feed			
Feed current draw	0.55 kW	Feed speed	7 m/min
Edges			
Edge thickness reel material	0,4 – 2,0 mm	Edge thickness strip material	0,4 – 3,0 mm
Pre-milling unit			
Pre-milling unit extraction port Ø	2 x 80 mm	Pre-milling unit current draw	2.2 kW
Pre-milling unit milling speed	9000 min^{-1}	Pre-milling unit diamond milling Ø	80 mm
Pre-milling unit milling height	56 mm	Pre-milling unit material removal	0.5 / 1 / 1.5 / 2 mm
Scraper blade units			
Radius scraper	2 mm		

Workpiece			
Workpiece thickness	8 – 50 mm	Minimum length of workpiece	120 mm
Min. work piece width	110 mm		
Product information EU 2023/2854			
Type of the generated data	Usage data	Format of the generated data	Common, machine-readable formats such as JSON
Amount of data	Up to 5 MB	Continuous data generation in real time	Yes
Data storage location	On the device and a remote server	Data access	On the device and physical and wireless interfaces
Further information	In the operating instructions or at info@stuermer-maschinen.de		

Equipment

Roller edge rotary platen	730	Pre-milling unit	with two slide cutters
Bonding unit	✔	Corner copy unit	✔
Combination unit flush trimming / rounding	✔	Flush radius milling unit	✔
Radius scraper unit	With numerical position display	Area scraper unit	With rotating copying device

Accessories



Diamond tools for jointing cutter

holzkraft Holzbearbeitungsmaschinen

Article number
5514565

Availability
No stock available
Information:
Next availability
Unknown

Purchase
Minimum 1 pc(s).

Price informations



Glue container
interchangeable for polyurethane glue with rapid drainage

holzkraft Holzbearbeitungsmaschinen


Article number
5514585

Availability
No stock available
Information:
Next availability
Unknown

Purchase
Minimum 1 pc(s).

Price informations

Options equipment



Buffing unit

holzkraft Holzbearbeitungsmaschinen

Article number
5514560

Availability
No stock available
Information:
Next availability
Unknown

Purchase
Minimum 1 pc(s).

Price informations



Edge heating device

Article number	Availability	Purchase	Price informations
5514579	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Anti-adhesive spray unit

Article number	Availability	Purchase	Price informations
5514580	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Tool Kit
Radius 3 mm

Article number	Availability	Purchase	Price informations
5514562	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Tool Kit
Radius 1.5 mm

Article number	Availability	Purchase	Price informations
5514563	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Tool Kit
Radius 1 mm

Article number	Availability	Purchase	Price informations
5514564	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Option grooving unit
Groove width 4 mm

Article number	Availability	Purchase	Price informations
5514571	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Solid wood edge magazine

Article number	Availability	Purchase	Price informations
5514561	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Quick change system glue container

Article number	Availability	Purchase	Price informations
5514575	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	

Glue container

Polyurethane glue with rapid drainage

Article number	Availability	Purchase	Price informations
5514586	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	

Ceramic lamp

With infrared rays

Article number	Availability	Purchase	Price informations
5514587	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	

Nesting sensing roller

Flush milling unit

Article number	Availability	Purchase	Price informations
5514588	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	

Nesting sensing roller

Scraper unit

Article number	Availability	Purchase	Price informations
5514589	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	



Interior lighting of the machine

Article number	Availability	Purchase	Price informations
5514590	No stock available Information: Next availability Unknown	Minimum 1 pc(s).	

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.