

NAXLANTIA

INSTRUCTION MANUAL

WARRANTY

Thunder Tiger guarantees this model kit to be free from defects in both material and workmanship. The total monetary value under warrant will in no case exceed the cost of the original kit purchased. This warranty does not cover any components damaged by use or modification. Part or parts missing from this kit must be reported within 60 days of purchase. No part or parts will be sent under warranty without proof of purchase.

To receive part or parts under warranty, the service center must receive a proof of purchase and/or the defective part or parts. Should you find a defective or missing part, contact the authorized Thunder Tiger Service/Distributor nearest you.

WARNING

The 1 meter America's Racing Yacht, its parts and its construction tools can be deadly weapons. Always exercise extreme caution when using this product. Improper operations may cause personal and/or property damage. Thunder Tiger and its distributor have no control over damages resulting from shipping, improper construction, or improper usage.

Thunder Tiger assumes and accepts no responsibility for personal and/or property damages resulting from the use of improper building materials, equipment, and operations. By the act of assembling this product, the user accepts all resulting liability. If the buyer is not prepared to accept this liability, then he/she should return this kit in new, unassembled, and unused condition to the place of purchase.

Notice

This is not a toy. Assembly and operating of this boat requires adult supervision.



No.5549

Introduction

Thank you for your purchase of the Thunder Tiger Naulantia, the 1M America's Cup Yacht. This yacht is both good for indoor display and outdoor sailing. With proper care taken during assembly, the Naulantia will provide you a good performance and long service life.

Please contact Thunder Tiger authorized distributor for tech support or customer service if you encounter any problem during the assembly.

Enjoy the sailing fun with Thunder Tiger Naulantia.

Items Required for Assembly

Radio

ACE JAGUAR 2 CH Radio is highly recommended(No.8216).

Features:

- AM Digital proportional control
- Available in 2 ch
- Unique Ergonomically Transmitter design
- Servo reversing
- CH1 & Ch2 Trims
- Adjustable Natural Position for Throttle
- LED Battery Level Indicator Light w/Low Power Flashing
- Easy Access Crystal
- External CHarging Jack for Rechargeable Battery



No.8216

Winch Servo

Introduction of Thunder Tiger Sail Winch Servo. This servo is specially design for 1M Yacht that torque is up to 11kg-cm, the speed is at 0.28sec/60 and max. rotation at 2 turns (720°). Standard quarter size with water proof seal between cases. All plastic gears. Comes with drum and mounting hardware. Fits to most sailing yachts in the market.

Specifications:

- Length: 58mm
- Width: 28mm
- Height: 52mm
- Weight: 120g
- Speed: 0.28s/60°
- Torque: 9.5kg-cm at 4.8V 11kg-cm at 6V



No.8141


Battery

AcePower NiMH 3600mAh 4.8V Battery Pack is recommended. High capacity for long time use and perfect fit in the hull radio compartment.



No.2980

Tools Required for Assembly




Needle Nose Pliers



Phillips Screwdriver, Med



Hobby Knife



Scissors



CA Instant Glue




Drill Bit
1/16", 1.6mm
5/64", 2mm
1/8", 3mm
5/32", 4mm

- Sandpaper (#400 grit)
- Rubbing Alcohol

Before Assembly


- Read all directions thoroughly before assembly.
- Check the parts against the parts drawing on page 3-4.
- When mixing epoxy, apply equal volume from two bottles.
- When tighten screws, be sure not to overtighten, as the metal thread will strip out or damage the fiberglass, plywood, plastic or Aluminum.

In each step, the needed parts are shown the number right below. Locate all parts for the steps.



Clear a place on your workbench or table, and let's begin.

Some Basic Knots



Bowline Knot





Figure Eight Knot



Reef Knot

SCALE
1:1



8 3x8 mm Sink Screw (6)



9 3x5mm Screw (1)



10 M4 Locknut (3)



11 M3 Locknut (4)



12 M2 Nut (9)



13 Ball (2)



1 4x32 mm Screw (1)



2 3x25 mm Wood Screw (2)



3 3x16 mm Wood Screw (4)



4 3x10 mm Wood Screw (9)




5 2x8 mm Wood Screw (18)



7 2x12 mm Screw (9)



14 Ball End (2)



15 Winch Line Guide (2)



16 End Cup A (1)



17 Rudder Tube (1)



18 Winch Line Guide B (2)



19 Wheel Collar (1)



20 Standoff (2)



21 End Cup B (3)



22 Keel Tube (1)



23 Clevis (1)



24 Steering Arm (1)




25 Silicone Tube (1)




26 Rudder Pushrod (1)




27 Swivel (8)



28 Foam Tube (2)



29 White String (1)



30 Black String (1)



31 PE String (1)



33 Tie Rod (1)



34 Winch Servo Cover (1)



35 O-Ring (3)



37 Rudder (1)



38 Keel (1)




39 Rudder Well Cover (1)




40 Ballast (1)




42 Mount (1)



41 Hull (1)




43 Hatch Cover (1)



45 Hatch Mount (1)



46 Mast A (1)



47 Mast B (1)



48 Mast Joiner (1)



49 Head Crane (1)



50 Main Boom (1)




51 Jib Boom (1)




54 PVC Strip (3/L)




55 PVC Strip (2/S)



57 Display Stand (2)




58 Al. Stand B (2)




59 Al. Stand A (4)



44 Bulkhead (1)




36 Servo Tray (1)




52 Jib Sail (1)


53 Main Sail (1)




60
61
62
63
64




66
67
68




89
90
91
92



79
80
81
82
83
84
85
86
87
88



70
71
72
73
74
75
76
77





65
69

1

Display Stand Assembly

3 28 41 56 57 58 59

1. Locate the display stand parts , then assemble the stand as shown at right. Use 3x16mm wood screw 3 to secure the Hull Support 57 and Al. Stand B 58. You may apply a thin bead of 5-min. epoxy at the joint before you insert the Al. Stand B.
2. Next Insert the other four Legs 59 and install the Feet 56. It is not necessary to apply any epoxy for these four legs and feet.
3. Locate the black Foam Tube 28 then use scissors to cut the foam tube so it can be installed on the hull support as shown. This will protect the hull bottom from scratches during construction and storage.
4. Now you can place the Hull 41 on the display stand during construction.




2

Keel Assembly

8 10 35 40 90 92

1. Thread the O-ring **35** onto the keel shaft.
2. Apply a generous amount of epoxy to the slot of Ballast Bulb **40** and insert the keel, securing with the M4 Locknut **10** by using the furnished small 4-way wrench. Wipe out the excess epoxy. Excess epoxy that over-flows the ballast bulb can be smoothed out with a wet finger, or removed using rubbing alcohol. This must be done before the epoxy hardens.
3. Secure the Stabilizer **92** or the half-pipe part **90** with the two 3x8mm Sink Head Screws **8**.





3

Keel and Rudder Tube Assembly

16 17 21 22

1. Insert the Keel Tube 22 from hull top and reach the hull bottom then epoxy the two End Caps 16 21 in place. There are three big end caps and one small end cap. The small one for the bottom hull. Note: end caps are working as waterproof and epoxy will help to fill the gap between cap and tube. Keel Tube might need to trim the length, to keep it level with the deck. However, do not leave any excess epoxy on the inside the tube as it will be difficult to insert the keel shaft if there is any hardened epoxy inside. Note: You may need to sand contact area A of the hull if tube is higher than the deck.

2. Using the same way to install Rudder Tube 17 and the other two end caps in place then allow the epoxy to cure.




4

Reinforced Bulkhead Assembly

44

1. Locate the bulkhead from the plywood part, trial fit the bulkhead in the hull and trim it if necessary.
2. Securing the bulkhead with epoxy as the shadow in the drawing. Make sure the bulkhead is firmly attached to the inside of the wall of the hull.
3. Upside down the hull and apply enough epoxy to the area of Mast Mount Well inside the hull so there is no gap in between the bulkhead and the Mast Mount Well is well secured.



5

Keel and Rudder Assembly


9 10 15 18 19 24 26 35 37

1. Drill 4mm hole at the dot then install the Winch Line Guide A **15** from the inside of the hull then secure Winch Line Guide A and B **18** together on the deck. Do the same procedure for the other winch line guide assembly.

2. Trial fit the keel in place, trim the contact area if necessary. Make sure the keel fit into the hull properly. Secure the keel shaft with M4 Locknut **10** by using the furnished 4 way wrench. The keel can make it inconvenient when moving the hull around during assembly.

3. Please use care when placing the hull on stand as the stabilizer will contact the AI. Stand B, it will need slightly to rotate the hull and let stabilizer go through the display stand.

4. Thread the O-ring **35** onto the rudder shaft. Install Rudder **37** in place by securing the Steering Arm **24** and Collar **19** with 3x5mm Screw **9**. Steering Arm need to be trimmed as indicated. In this step you will need to connect the Pushrod **26** by threading the Z-bend end to steering arm first then thread the other end to the hull so you can secure the arm with collar inside to the rudder shaft as illustration. Note: the pushrod and rudder should perpendicular to the steering arm.





6

Hatch Cover Assembly II

- 4 5 25 43 66 67 68 77
81 84 85 86 87 88

1. Install the Silicone Tube **25** underneath the hatch cover **43** as illustration. Start from steering wheel end then push in the silicone tube in place. Try to smoothen the tube as you can. Hint: Avoid of pulling or squeezing too much of the silicon tube. Also do not cut away silicone tube.
2. Install Steering Wheel **66 67 68** three parts together by using CA instant glue. Set it aside and wait final assembly.
3. Glue Winch **84 85**, Steering Wheel Stand **86 87** and Main Sheet Winch Stand **88** in place.
4. Secure the wheel stand with 3x10mm Wood Screw **4**, next secure the Winch **77** on the Main Sheet Winch Stand.
5. Secure the steering wheel assembly on stand with 2x8mm Wood Screw **5**.
6. Install the Winch Handle **81** in place, adjust the handle evenly then apply tiny CA at the joint.
7. After you done all adjustment and Rigging, attach the hatch cover assembly in place.




7

Hull Fittings Assembly

- 4 5 8 11 45 65 69 70
71 72 76 77 79 81 82 84

1. Drill four 3mm(1/8") hole at the dots around the hull opening. Next secure the Hatch Cover Mount 45 with 3x8mm Sink Head Screw 8 and M3 Locknut 11 .
2. Install all Winches 72 76 77 as shown, you will need to drill 2mm(5/64") hole at the dot and secure the winches with 3x10mm Wood Screws 4 .
3. Drill 1.6mm(1/16") hole at each dot for Chain Plates 70 71, secure the chain plates with 2x8mm Wood Screws 5 .
4. Drill 1.6mm(1/16") holes for Winch 84, CA the winch in place next glue the handles 81 .
5. Drill 1.6mm(1/16") holes for Aerial Frame 69 79, install the Aerial Frame in place as shown.
- F. Drill 2mm(5/64") hole at each dot for Rail 65, trial fit the rail then apply CA glue to secure the rail in place.
- G. Drill 2mm(5/64") hole for the decoration 82, CA this part firmly on deck.




8

Servo Tray Assembly

36

1. Locate the die-cut plywood sheet 36 then use thick CA to assemble the servo tray as shown.
2. Slightly sand the glue area inside the hull then apply enough epoxy to glue servo tray in the hull. Note the position will be about 2mm (5/64") from the edge to the hatch opening if you see from the top vertically. Suggest to use sandpaper to sand the glue area, this will enhance the adhesion.



9

Main Mast Assembly

1 5 7 10 12 13 14 33
 46 47 48 50 60 61 62 63
 64 70 73 75 89 91

1. Secure the two Ends 89 91 onto the Main Boom 50 with 2x8mm wood screw 5 .

2. Secure the Chain Plate 70 on the main boom with 2x8mm wood screw 5 .

3. Secure the Ball 13 on the boom with 2x12mm Screw 7 .


4. Assemble and Main Mast A 46 and B 47 with the Mast Joiner 48 and Boom Joiner 75 . Secure the boom joiner with 2x12 mm Screw 7 and M2 Nut 12 .

5. Install all Spreaders 60 61 62 63 64 in place as illustration with 2x12mm Screw 7 and M2 Nut 12 . Do not over-tighten the nut as it may damage the mast.

6. Install the ball on Tie Rod Base 73 with 2x12mm Screw 7 and M2 Nut 12 . Next secure the base at the bottom of main mast with 2x8 mm Wood Screw 5 .

7. Install the main boom on the boom joiner with 4x32mm Screw 1 and M4 Nut 10 . Keep the main boom rotates freely.

8. Assembly the Tie Rod 33 with two Ball Ends 14 as illustration. Note the "Tiger" marks are either way at two ends. The "Tiger" mark always faces up when pushing the ball end to the ball.




10

Main Sail Attachment

30 31 49 53 54

1. Apply PVC Strip **54** on the Sail **53** in the position as illustration. Note: Apply at the back side is suggested. These Strip will reinforce the sheet.
2. Thread the PE String **31** in the sheet, next slide the leading edge of main sail into top groove of the mast.
3. Pull the sail all the way to the root of the mast then install the head crane **49** in place. Make sure that all the leading edge of sail is smooth and securely in the groove of mast.
4. Now you may tie the sail with the Black String **30** on the boom and head crane. Reef knot is suggested.



11

Main Sail Rigging

27 30 80

1. Cut 7 pieces Rigging Strings 80 into the lengths as shown for use in this step.

Jump String A x 1	48"(120cm)
Jump String B x 2	38"(95cm)
Mast String C x 2	52"(130cm)
Mast String D x 2	16"(40cm)

2. Jump String A

Thread the jumper string A from the second spreader root through the first spreader tip, head crane, the first spreader tip and finally back to the second spreader root. Try to adjust the string as tight as possible and make both two Figure Eight knots at the second spreader root.

3. Jump String B

Make a Figure Eight knot then thread Jump String B from second spreader tip to the other side of the third spreader tip, the other side of fourth spreader tip then the other side of the fifth spreader tip. Adjust the tension and make the same knot. Do the same procedure for the other Jump String B.

4. Mast String C

Make a Figure Eight knot then thread Mast Rigging String C from the first spreader root through the second spreader tip, the third, the fourth and the fifth spreader tip.

Thread the string through the first hole of String Adjuster 80, then the second hole. Next thread through the Swivel 27 then the third hole. Make a Bowline knot.


Keep adjuster is about 10cm to the swivel.

Do the same procedure on the other Mast Rigging String C.

5. Mast String D

Make a Figure Eight knot then thread Mast Rigging String D from the fifth spreader root then do the same way on the string adjuster and swivel.

Do the same procedure on the other Mast String D.



12

Jib Boom and Jib Sail Assembly

5 30 51 52 55 74 83


1. Place the plastic Slider **74** on the boom **51** as illustration then secure the slider at the second hole with 2x8mm Wood Screw **5**.

2. Place the other slider on the other boom end then insert the Jib Boom End **83**. Next secure the slider and jib boom end together with 2x8mm Screw **5**.

3. Epoxy the other Jib Boom End in place. Note the orientation of the ring.

4. Apply PVC Strip **55** on the Jib Sail **52** in the position as illustration. Note: Apply at the back side is suggested.

5. Use Black String **30** to tie the jib sail on the boom. Reef knot is suggested.




13

Jib Sail Attachment

27 30 80

1. Tie a Swivel **27** at the jib boom control slider with Black String **30** as illustration.
2. Cut a piece of string in length of 10" (25cm) then secure the jib sail on Mast Joiner as shown.
3. Backstay String
Cut a piece of string in length of 63" (160cm) then make a Bowline knot at the head crane tip. Do the same way as mast rigging line to thread string to Adjuster **80** and Swivel **27**.



14

Radio Installation I

29

1. First cut two sail control lines 29.

Main Sail Control Line 39"(100cm)
Jib Sail Control Line 39"(100cm)

2. Thread the control lines through front and rear winch line guides then try to reach the line inside the hull. Temporarily secure the two ends on the deck and servo tray with tape to prevent the line loosened.



3. Refer to servo manual and install the servo mounting hardware then secure the servos in place. Note the servo orientation.

4. Install the switch in place.

5. Connect the radio system following the manufacturer instructions. Place the receiver in the radio compartment at the right side of servo tray.

6. The Sub-C 4-cell 3000~4000mAh battery is recommended (No.2980) which you can place in battery holder.

7. Tape the receiver antenna wire to underside of the deck then thread the antenna to the rudder steering well.



15

Radio Installation II

② ②① ②③ ②⑦ ③④ ③⑨ ④② ④③

1. Thread a Metal Clevis ②③ on the pushrod. Attach the clevis to the servo arm. Adjust the clevis so that the servo arm and rudder steering arm are at ninety-degree angle to the pushrod when servo is in neutral position. Attach the rudder cover decal ④③ on the rudder cover ③⑨ then drill (5/64")2mm hole for antenna to go through. Thread antenna and attach the cover in place.


2. Epoxy the Mast Mount ④② in place. Make sure there is no epoxy inside the mast mount A as the Mast will install in later. Epoxy the keel in bottom slot and whole mast mount is recommended if user would enhance the performance, however, the weakness is the keel can not be removed.

3. Thread one end of the Jib Sail Control String to the servo drum. Make a Figure Eight knot in the drum. Turn on the radio and make sure the control stick is full down then wind the string for two turns in the drum then place the drum on the winch servo.

4. Tie a Bowline knot to the Swivel ②⑦ on the other end of the control string. Keep the string about 1/8" (3mm) out of the front winch line guide. Note: The less turns of string in the drum the less chance for string to be out of the groove.

5. Do the same procedure on the Main Sail Control String but keep the string about 1-5/8"(40mm) out of the rear winch line guide.


6. Do the sail adjustment in page 21, after you satisfied with the adjustment then secure the drum with the screw comes with the servo. Next secure the Winch Servo Cover ③④ with two Standoff ②① and 3x25mm Wood Screw ②. You will need to trim a notch for the string to go.



16

Attaching the Rigging Snaps

1. Attach the main mast assembly to the main mast mount.
2. Snap on all the mast rigging swivels to the chain plates as shown.
3. Adjust the string adjusters so main mast can stand up.
4. Attach jib boom swivel to the bow chain plate. Adjust the jib sail adjuster at the top so mast is vertical.
5. Attach the main sail and jib sail control lines to the main boom and jib boom respectively.
6. Snap on the swivel of backstay string to the stern chain plate. Adjust the string adjuster. Do not adjust the string too tight as head crane might be too low to contact the sail.
7. Trim the number decal then refer to color box and apply on the sheet.



17

Adjustment

1. Sail Adjustment

A. When the sail winch transmitter control stick is in the full “down” position, the sail winch servo drum should rotate and the sail control lines are tight. Jib sail and main sail now are at about 0-degree. If not, you may adjust the string length.

B. With winch drum is in the “full up” position, open the main boom to a deflection of about 80-degree.


C. It will be necessary to readjust the “full down” setting again, as both of these adjustments are effected by one another. The goal is to reach the best compromise possible.

D. Normally use the trim on transmitter will help the adjustment. If use a quality radio which has end position adjustment function then it will be much easier to adjust sail angle.

E. If user use other servo then the control throw might vary. In this situation, user will have to change the position of the Chain Plate on Main Boom and the Slider on Jib Boom. Drill 1/16” holes at the desired position then use furnished 2x8mm wood screw to secure the slider and the chain plate.

2. Rudder Adjustment:

Make sure that the rudder deflects 30-degree in each direction. If it does not, move the clevis closer to the center of the servo arm.





Preparations for Sailing

Before sailing your Naulatia for the first time, take note of the following:

- A. Using clear tape, seal the radio hatch cover after turning on your radio to prevent water from entering the hatch.
- B. Make sure that your transmitter antenna is extended completely. Make sure that the receiver antenna is completely uncoiled (either inside or outside the hull).
- C. Always turn the transmitter on before the receiver, likewise, turn the receiver off before the transmitter.
- D. Check that each sail, line, snap, and fitting is properly installed and adjusted.


CAUTION:

Periodically check all knots if loose and the inside of the hull to make sure that there is no excessive accumulation of water. Suggest to test the boat in light wind. Naulatia has bigger sail so stronger wind will bend the boat very much, properly control the angle of main sail and operate the yacht in light wind (1~2M/sec) is recommended.




Tuning your Naulantia for Proper Operation

Straighten any left or right leaning of master




Tighten or slacken the adjuster in order to straighten the mast.

Straighten any forward or backward inclination of master




1. If your boat carries weather helm, incline the mast a bit forward.
 2. If your boat carries lee helm, incline the master a bit backward.
- Refer to the explanation of weather helm and lee helm below




Maintaining an optimum sail profile is important for both speed and control. You may need to make some finer adjustments to your tuning to obtain the sail profile you want. The sail profiles shown in the figure are viewed from behind.

Mast Adjusting



Weather Helm and Lee Helm


With the Rudder in line with the Keel, if the boat tends to turn windward, it is said that the boat carries weather helm. If it tends to turn leeward, it is said that it carries lee helm. The situation in which the boat shows neither tendency is called balanced helm. In general, a boat carrying a slight weather helm is better in performance than one carrying lee helm or having balanced helm. Therefore, after adjusting the boat to balanced helm re-adjust it so that it carries slight weather helm.



Starboard Tack and Port Tack

The right side of the boat is called starboard and the left side of boat s called port. When the yacht sails with the wind cross the starboard and the mainsail is on the port side, it is said that the boat is on a starboard tack. When it sails with the wind cross the port and with the mainsail on the starboard, it is said that boat is on a port tack. You can sail on a starboard or port tack when sailing close-hauled (i.e. windward), wind abeam (i.e. leeward).

Principle of Sailing



Wind abeam
Sails: each at a position of 45°
Rudder: in center position

Quarter lee
Sails: letting both out a little more
Rudder: to the left

Starboard tack-running
Sails: letting both out to their maximum position
Rudder: in center position

Port tack-running
Sails: letting both out to their maximum position
Rudder: in center position

Quarter lee
Sails: pulling both in a little
Rudder: in center position

Luffing up
Sails: pulling in bit by bit
Rudder: to the left

START
Wind abeam
Sails: each at a position of 45°
Rudder: in center position

Port tack - close - hauled
Sails: keeping pulled in
Rudder: to be held at the center as long as the sails do not shiver

Tacking
Sails: keeping pulled in
Rudder: to the right

Bearing away
Sails: let both out so as not to shiver
Rudder: to the left

Tacking
Sails: keeping pulled in
Rudder: to the left

Starboard tack - close - hauled
Sails: keeping pulled in
Rudder: to be held at the center as long as the sails do not shiver

Tacking*
Sails: keep pulled in
Rudder: to the left

Port tack - close - hauled
Sails: keep pulling in
Rudder: to be held at the center as long as the sails do not shiver


Luffing up
Sails: pulling both in all the way
Rudder: to the left

45°



Other Tips

- * Sail your boat only in still bodies of water. Never sail your boat in running water such as streams or rivers or sea, as it is easy to lose control of your boat.
- * Do not sail the boat in very heavy winds.
- * If you will be operating your boat in the same area as other R/C craft, be sure that you are all on different frequencies to help avoid any mishaps.



**PJ6318-R
PJ6318-L Hull
PJ6318-Y**



End Cup A (1)



End Cup B (3)



Keel Tube (1)



Rudder Well Cover (1)




Rudder Tube (1)



Winch Line Guide A (2)




Winch Line Guide B (2)




Hull (1)

PJ6052 Decoration Set A




Chain Plate (1)


PJ6053 Decoration Set B



Railing (1)



Steering Wheel (1)




Winch (1)

**PJ6319-R
PJ6319-L Sails
PJ6319-Y**




PVC Strip (L/3,S/2)



Jib Sail (1)

Main Sail (1)

PJ6055 Rudder Linkage



Steering Arm (1)



Wheel Collar (1)



3x5mm Screw (1)



Clevis (1)




Rudder Pushrod (1)

PJ6245 Head Crane




Head Crane (1)

PJ6058 Spreader




Spreader (1)

PJ6073 Rigging String




White String (1)



Black String (1)



PE String (1)



Boom End & Stabilizer (1)

PJ6061 Boom Retaining Set

Tie Rod (1)



Ball End (2)



Ball (2)

PJ6062 Swivel



Swivel (8)

PJ6063 Winch Servo Horn Cover




Standoff (2)




Winch Servo Cover (1)


PJ6064 Boat Stand



Display Stand (2)



Al. Stand A (4)



Al. Stand B (2)



3x16 mm Self-tapping Screw (4)

PJ6065 Screw



M4 Locknut (1)



3x8 mm Sink Screw (4)



3x10 mm Self-tapping Screw (9)



2x12 mm Wood Screw (9)



2x8 mm Self-tapping Screw (18)



M3 Locknut (4)



3x25 mm Self-tapping Screw (2)




4x32 mm Wood Screw (1)



M2 Nut (9)

PJ6067 Foam Tube




Foam Tube (2)

PJ6066 Rudder



Rudder (1)

PJ6068 Servo Tray



Servo Tray (1)



Bulkhead(1)


PJ6070 Keel



Ring (3)



M4 Locknut (2)




Keel (1)

PJ6071 Boom



Jib Boom (1)



Main Boom (1)


PJ6056 Hatch Cover



Silicone Tube (1)



Mount (1)



Hatch Cover (1)



Hatch Mount (1)


PJ6054 Mast



Mast A (1)



Mast Joiner (1)



Mast B (1)

PJ6059 Ballast



3x8 mm Sink Screw (2)



Ballast (1)

AMERICA'S CUP RACING YACHT

No.5549

Specifications:

Length: 39"(993mm)

Beam: 6.75"(172mm)

Sail Area:744sq.in.(48dm²)

Mast Height: 51.4"(1306mm)

Overall Height: 67"(1700mm)

Overall Weight: 3.5 Kg(7.7 lb.)

